

PRODUCT INFORMATION

CEVO®-protect O-2316

Product Description

CEVO®-protect O-2316 is a mixture of hydrocarbon waxes and polymers.

General Advantages

Provides protection from humidity/moisture and gives chemically resistant coatings.

Examples of Use

- Edge protection wax, coating wax for cardboards/cardboard stand-ups
- Stop-off wax/wax maskant for metal coating/electroplating applications

Delivery Specifications *

Characteristics	Unit	Target value	Method
Drop point *	°C	63 – 68	ASTM 3954
Colour	–	white	AA 3.2.1.505
Viscosity @ 120 °C	mPas.	approx. 8 – 15	AA 3.2.1.520
Density	g/cm ³	approx. 1.00 – 1.02	Ph. Eur. 2.2.5

Packaging and Handling

Physical form	Pastilles
Packaging	Paper bag or Big Bag
Storage	Store at ambient temperature on a dry place. Protect from heat/overheating and direct sunlight. The maximum shelf life is 5 years after production. Thereafter, tests of the chemical characteristics are recommended. After delivery, a minimum remaining shelf life at the customer of 1.5 years is warranted.

Safety

CEVO®-protect O-2316 is not classified as carcinogenic, mutagenic or reprotoxic; no health or environmental hazards are known, provided it is applied in industrial and professional settings.

For more information, consult SDS.

Delivery Time and Availability

Standard delivery time: 2 – 3 weeks. Preconditions can be met for achieving shorter delivery times on standard products when demanded by the market.

Legislation

Food contact legislation:

- Product for technical applications

Other legislation:

- REACh, RoHS and CONEG compliant
- Ingredients listed in all relevant national inventories

For further information, please contact application@voelpker.com.