

PRODUCT INFORMATION

CEVO®-stab F-5510

Product Description

CEVO®-stab F-5510 is a special one pack that includes a synergistic combination of different lubricating and dispersing agents as well as a balanced mixture of diverse stabilisers.

General Advantages

The mixture was engineered especially for the recycling processes of POM Copolymer (reinforced and unreinforced) waste.

Examples of Use

By the addition to the formulations the thermo-oxidative force of polymer during extrusion process will be minimised and the package works as scavenger for formed formaldehyde.

We recommend to add amounts of 0.4 – 0.6 %.

Delivery Specifications *

Characteristics	Unit	Target value	Method
Melting point *	°C	> 120	ASTM 3954
Colour	–	white	AA 3.2.1.505
Density	g/cm ³	1.00 – 1.02	Ph. Eur. 2.2.5

Packaging and Handling

Physical form	Compactate
Packaging	Paper bag
Storage	Store at ambient temperature on a dry place. Protect from heat/overheating and direct sunlight. The maximum shelf life is 5 years after production. Thereafter, tests of the chemical characteristics are recommended. After delivery, a minimum remaining shelf life at the customer of 1.5 years is warranted.

Safety

CEVO®-stab F-5510 is not classified as carcinogenic, mutagenic or reprotoxic; no health or environmental hazards are known, provided it is applied in industrial and professional settings. See SDS.

Delivery Time and Availability

Standard delivery time: 4 weeks. Preconditions can be met for achieving shorter delivery times on standard products when demanded by the market.

Legislation

Product for technical applications.

- REACH, RoHS and CONEG compliant
- Ingredients listed in relevant national inventories

For further information, please contact application@voelpker.com.