

PRODUCT INFORMATION

CEVO®-mold I-6628

Product Description

CEVO®-mold I-6628 is a special wax blend based on natural regrowing acid- and ester waxes.

General Advantages

Good release effect on phenolic resins.

Examples of Use

- Release agent, e.g. for phenolic resins and plastics; low melting
- Lubricant for PE/WPC

Delivery Specifications *

Characteristics	Unit	Target value	Method
Acid value *	mg KOH/g	140 – 185	ISO 2114
Saponification value	mg KOH/g	170 – 210	ISO 3681
Drop point *	°C	55 – 65	ASTM 3954
Colour	–	brown	AA 3.2.1.505
Viscosity @ 120 °C	mPas	approx. 5	AA 3.2.1.520

Packaging and Handling

Physical form	Pastilles or flakes
Packaging	Paper bag or Big Bag
Storage	Store at ambient temperature on a dry place. Protect from heat/overheating and direct sunlight. The maximum shelf life is 5 years after production. Thereafter, tests of the chemical characteristics are recommended. After delivery, a minimum remaining shelf life at the customer of 1.5 years is warranted.

Safety

CEVO®-mold I-6628 is not classified as carcinogenic, mutagenic or reprotoxic; no health or environmental hazards are known, provided it is applied in industrial and professional settings.

For more information, consult SDS.

Delivery Time and Availability

Standard delivery time: 2 – 3 weeks. Preconditions can be met for achieving shorter delivery times on standard products when demanded by the market. Please contact us for your individual requirements.

Legislation

Food contact legislation:

- Product only for technical applications

Other legislation:

- REACH, RoHS and CONEG compliant
- Ingredients listed in relevant national inventories

For further information, please contact application@voelpker.com.