

PRODUCT INFORMATION

CEVO®-stab A-1310

Product Description

CEVO®-stab A-1310 is a one pack and it includes a synergistic combination of lubricating and dispersing agents as well as a UV stabiliser.

General Advantages

The package was engineered especially for the use in polyamide compounds stabilised for outdoor applications.

Examples of Use

The package can be used in unfilled, mineral-filled or glass fibre reinforced as well as impact-modified formulations. The UV stability of produced compound is increased and in addition it improves the homogeneity of the filler/modifier distribution, reduces damages by friction peaks and leads to an improved surface quality.

We recommend using amounts of 0.5 – 0.7 %.

Delivery Specifications *

Characteristics	Unit	Target value	Method
Melting point *	°C	> 80	ASTM 3954
Colour	–	slightly yellowish	AA 3.2.1.505
Density	g/cm ³	1.00 – 1.02	Ph. Eur. 2.2.5

Packaging and Handling

Physical form	Powder
Packaging	Paper bag
Storage	Store at ambient temperature on a dry place. Protect from heat/overheating and direct sunlight. The maximum shelf life is 5 years after production. Thereafter, tests of the chemical characteristics are recommended. After delivery, a minimum remaining shelf life at the customer of 1.5 years is warranted.

Safety

CEVO®-stab A-1310 is not classified as carcinogenic, mutagenic or reprotoxic; no health or environmental hazards are known, provided it is applied in industrial and professional settings.

Delivery Time and Availability

Standard delivery time: 2 – 3 weeks. Preconditions can be met for achieving shorter delivery times on standard products when demanded by the market.

Legislation

Food contact legislation:

- Product for technical applications

Other legislation:

- RoHS and CONEG compliant
- Ingredients listed in all relevant national inventories

For further information, please contact application@voelpker.com.