PRODUCT INFORMATION

CEVO®-protect O-6628

Product Description

CEVO®-protect O-6628 is a special wax blend, based on natural regrowing waxes and ester waxes.

General Advantages

Gives good hydrophobicity and dark pull-up effects.

Examples of Use

Leather finishing/conditioning and softening of the leather: pull-up wax for heated roller coater application; gives dark pull-up effects and good hydrophobicity. CEVO®-protect O-6628 is miscible with paraffin and paraffin oil or neatsfoot oil.

Delivery Specifications *

Characteristics	Unit	Target value	Method
Acid value *	mg KOH/g	140 – 185	ISO 2114
Drop point *	°C	65 – 75	ASTM 3954
Saponification value	mg KOH/g	approx. 170 – 210	ISO 3681
Colour	–	yellow	AA 3.2.1.505
Viscosity @ 120 °C	mPas	approx. 50	AA 3.2.1.520

Packaging and Handling

Physical form	Pastilles or flakes
Packaging	Paper bag or Big Bag
Storage	Store at ambient temperature on a dry place. Protect from heat/overheating and direct sunlight. The maximum shelf life is 5 years after production. Thereafter, tests of the chemical characteristics are recommended. After delivery, a minimum remaining shelf life at the customer of 1.5 years is warranted.

Safety

CEVO®-protect O-6628 is not classified as carcinogenic, mutagenic or reprotoxic; no health or environmental hazards are known, provided it is applied in industrial and professional settings.

For more information, consult SDS.

Delivery Time and Availability

Standard delivery time: 2 – 3 weeks. Preconditions can be met for achieving shorter delivery times on standard products when demanded by the market.

Remark: Voelpker's R&D department is permanently developing new special wax blends for the preparation of solvent-based dispersions. Please contact us for your individual requirements.

Legislation

Food contact legislation:
- Product for technical applications

Other legislation:
- REACH, RoHS and CONEG compliant
- Ingredients listed in all relevant national inventories

For further information, please contact application@voelpker.com.

The information contained herein is believed to be accurate and reliable as of the date issued. However, we do not warrant or guarantee the accuracy or reliability, in particular not for any specific intended use by the customer. It is the responsibility of those to whom we supply our products directly or indirectly to ensure that their use of the products complies with existing regulations, laws, legislations and proprietary rights. The information given by Völpker Spezialprodukte does not exempt the customer from carrying out inspections and analyses on goods purchased.

Issued: 2021-08-10, supersedes all previous editions

Völpker Spezialprodukte GmbH · Fabrikstraße 1 · 39393 Völpke · Germany · Telephone +49 39402 962-0 · www.voelpker.com